

SAFETY GATES

When Safety Matters

Intrepid Safety Gates

Manufactured from premium grade rigid polyurethane, the Intrepid self-closing gates provide long, low maintenance service life, even in the harshest of environments.

The unique design of the Intrepid gate has a horizontal swing instead of a vertical drop. The design relies solely on gravity. It does not depend on springs, cams, bearings or the operator.

Available in 4 standard widths to suit various opening sizes the Intrepid self-closing gates are easy to install. If you have an opening size that does not exactly suit the standard width gates, don't worry, the gates are easily cut to size. Being manufactured with no metallic parts, you will not require any hot work permits.

The unique hinge design of the Intrepid gates allows for the gate to open either to the right or the left making it the most versatile safety gate on the market.

All Intrepid gates are manufactured with high visibility safety yellow pigment throughout all the components.

Instant Set Polymer (ISP) is a solid polyurethane material developed in the mid-1970's. It takes its name from the fact that it is created by mixing two liquid components which react to form a solid material in less than a minute!

The final product is rigid, tough, and strong with excellent fatigue resistance. Being a plastic, it also has good electrical insulating properties and resists atmospheric corrosion.



Intrepid Self-Closing Safety Gate

- 4 Standard sizes
- Opens both **Left** or **Right** handed
- Non-Corrosive
- No springs or cams
- Fatigue Resistant
- UV Stabilised

Specifications

| Model | UDG22 | UDG27 | UDG32 | UDG37 |
|----------------------|-------------------------|-------|-------|-------|
| To Suit Opening (mm) | 560 | 690 | 820 | 950 |
| Working Temperature | From -40° C up to 80° C | | | |
| Colour | Safety Yellow. | | | |

Installation Kits

With the help of one of our installation kits, the UDG Safety Gate also easily attaches to either round or square pipe making installation easy.



Contact Us

Please give us a call for more information about our products and services

FRP Engineering
28 Baile Road
Canning Vale

Perth, 6155

Western Australia

P +61 (0)8 9455 4343

F +61 (0)8 9455 4373

enquiries@frpengineering.net

www.frpengineering.net

FRP Engineering Pty Ltd © Copyright 2015

DISTRIBUTED BY :



Head Office:
4 Monterey Rd Dandenong
Victoria 3175 Australia

Perth Office:
28 Baile Rd Canning Vale
Western Australia 6155
Phone: 1 800 236 337

A Bending Company
Phone: +61 3 9706 4440
Email: sales@abending.com
Web: www.abending.com

Kazed Industrial Solutions
Phone: 1800 236 337
Email: sales@kazed.com.au
Web: www.kazed.com.au